

# Regupol® 6015 H, 7 mm

Revision date: 01/01/07

Printing date: 04/01/07

<b>1. Application</b>	Elastic base mat for indoor flooring
<b>2. Product</b>	Name of Product : Regupol 6015 H  Colour : black  Material : elastic premanufactured mat made from selected rubber bound with polyurethane  Thickness : 7 mm
<b>3. Technical Data</b>	Specific Weight : 650 kg/m <sup>3</sup>  Weight per m <sup>2</sup> : 4.55 kg  Tensile Strength : 0.6 N/mm <sup>2</sup> DIN 53 571 B      Specimen  Elongation at Break : 65%      DIN 53 571 Specimen B  Tear Resistance : 4.0 N/mm      DIN 53 515

	<p>Stress at 25%</p> <p>Compression : 0.55 N/mm<sup>2</sup>      DIN EN ISO 3386-2</p> <p>Deformation by</p> <p>Compression : 1.60 N/mm<sup>2</sup></p> <p>Temperature Resistance : - 40° C up to 115° C</p> <p>Fire Resistance : Class B 2      DIN 4102</p>
<b>4. Notice</b>	<p>The above mentioned test data are based on periodical laboratory testing of test specimen taken from the actual manufacturing process and show the average values measured. The publishing of these technical data does not relieve the user of the</p> <p>necessity to test the relevant product for physical fitness based on a specific application. As the final use and application of our products are out of our control, this is the sole responsibility of the buyer / end user. All of our products do carry a warranty against manufacturer's defects according to our standard terms and conditions of sale. Due to deviations in raw materials, external influences like temperature and humidity variations, and the fact that this data relates to a resilient material, the above mentioned values are subject to vary up to +/- 25%.</p>